



June 1, 2021

Grade 1



Dillon





Flax



Steel



Snow



Lucid




Storm



Quarry



Graphite



Stratus



Iron



Balsa



Safari



Tusk



Black



Sandy



Straw



Buff



Flax



Baltic



Luggage




Fiesta



Cordovan



Nimbus



Apple Green



Chili



Lipstick



Williamsburg



Sage



Bordeaux



Brownstone



Thunder



Ocean



Grape



Java

Dillon

Content:	100% Polyurethane
Backing:	70% Polyester, 30% Cotton
Finish:	Antimicrobial -- silver ion technology
Weight:	20.16 oz. per linear yard
Width:	54"
Abrasion:	Heavy Duty - Exceeds 200,000 Cycles (Wyzenbeek - Cotton Duck Abradant) (ASTM D4157)
Light Fastness:	Class 4/200 hrs. min. (AATCC 16A)
Color Fastness:	Class 4 (ASTM D3597, AATCC 8) Wet Class 4 (ASTM D3597, AATCC 8) Dry
Physical Properties:	112 lbs. warp, 70 lbs. weft (ASTM D5034) Breaking Strength 92 lbs. warp, 77 lbs. weft (ASTM D4034) Seam Slippage 50,000 cycles (CFFA 10 Flex Resistance) Pass (CFFA 6a) Cold Crack ISO 1419 - Pass 5 weeks
Passes:	California Tech. Bulletin #117-2013 UFAC Class I NFPA 260 Class I MVSS 302 Pass IMO A. 652(16) 8.2
Cleanability:	WS - Both water and solvent based solutions.



14815 Radburn Avenue • Santa Fe Springs, California 90670
562-802-0464 • customerservice@ocisitwell.com • ocisitwell.com